

Casement Windows

ALUMINIUM WINDOWS – VIC



A beautiful design that compliments both traditional and modern décor & designed to maximise the opening window area.



Size Range (n1-n5)

STUD OPENING			670	910	1270	1270	1510	1510	1870	2110	2470	2710
BRICKS			2½	3½	5	5	6	6	7½	8½	10	11
WINDOW			610	850	1210	1210	1450	1450	1810	2050	2410	2650
920	10	857	DC0906	DC0909	DC0912a	DC0912b	DC0915a	DC0915b	DC0918	DC0921	DC0924	DC0927
		1090	DC1006	DC1009	DC1012a	DC1012b	DC1015a	DC1015b	DC1018	DC1021	DC1024	DC1027
1260	14	1200	DC1206	DC1209	DC1212a	DC1212b	DC1215a	DC1215b	DC1218	DC1221	DC1224	DC1227
		1435	DC1406	DC1409	DC1412a	DC1412b	DC1415a	DC1415b	DC1418	DC1421	DC1424	DC1427
1520	17	1457	DC1506	DC1509	★DC1512a	★DC1512b	★DC1515a	★DC1515b	DC1518	★DC1521	★DC1524	★DC1527
		1860	DC1806	DC1809	DC1812a	DC1812b	DC1815a	DC1815b	DC1818	DC1821	#DC1824	#DC1827
1860	21	1800	#DC1806FH	#DC1809FH	#DC1812aFH	#DC1812bFH	#DC1815aFH	#DC1815bFH	#DC1818FH	#DC1821FH	#DC1824FH	
		2120	DC2106	DC2109	DC2112a	DC2112b	DC2115a	DC2115b	DC2118	DC2121	#DC2124	#DC2127
2120	24	2057	#DC2106FH	#DC2109FH	#DC2112aFH	#DC2112bFH	#DC2115aFH	#DC2115bFH	#DC2118FH	#DC2121FH	#DC2124FH	
		2120	DC2106	DC2109	DC2112a	DC2112b	DC2115a	DC2115b	DC2118	DC2121	#DC2124	#DC2127

Note: For higher wind ratings, wind load graphs must be consulted. Not suitable for double glazing.

Optional Alternatives

							Key ★ NOT FOR N4 OR N5 # NOT FOR N5
Casement R.H. Hinge	Fixed Light/Casement	Fixed Light/Fixed Light	All Casement	Colonial C1	Colonial C2	Flyscreens (Manor only)	

Features

- Durable low maintenance, easy-clean aluminium profiles.
- Integrated tubular mullions and transoms with concealed fixing for superior strength.
- Full width winder support for improved aesthetics.
- Solid extruded aluminium sash corner stakes.
- Low E glazing optional for increased energy efficiency.
- Sealed casement stays for improved durability and smooth operation.
- Full perimeter sash seals for positive sealing.
- Fully open sash position allows external glass cleaning from inside.
- Moulded end gaskets at all frame joints.
- Full length under-sill flap for neat finish and allowance for building settlement (optional).

Hardware Options

- Cam locks fitted as standard.
- Optional Key lock available.